



### Features

- Easy to assemble
- Low standby power to save battery – mono switch brightness control
- Uses the latest powerful LEDs
- Impact-proof polycarbonate casing – drop tested to two metres

### Applications

Suitable for indoor or outdoor working environments as well as activities such as camping or hiking.



Part no,	ML-H10BCC	ML-H20BCC	ML-H30BCC	ML-H40BCC	ML-H50BCC
Power (W)	10	20	30	40	50
Lumen (Lm)	600	1300	2300	3000	4000
Power source	25.2Wh Lithium rechargeable battery				
Light source	Epistar LEDs				
Housing	Polycarbonate casing with aluminium substrate				
Housing colour	Yellow				
LED array	12 LEDs	24 LEDs	24 LEDs	32 LEDs	42 LEDs
Colour temp	Cool white, 5700k				
Operating temp	-30°C ~+ 80°C				
CRI (%)	>75				
Product weight	2.15kg				
Product size (mm)	Height: 245 Width: 215 Depth: 185				
Box dimensions (mm)	Height: 255 Width: 245 Depth: 155				
IP rating	65				
Lifetime	Up to 50,000 hours				
Warranty	2 years				



RoHS

At Ecoglow, we consider market feedback and continually improve our products. Specifications can change, so please check our website to confirm the latest specifications for this product. All electrical work must be performed by a qualified electrician.